HF-918/B3

Smart Equipment High Speed Crochet Machine

It is suitable for producing all kinds of elastic and non-elastic belts, bra lace belts, medical bandages, clothing belts, zipper belts, sports belts, etc.





Operating width			918	mm	
Corresponding	Needle	15	18	20	24
number of stitches	Needle position	540	630	720	840
Bar number of weft		3 PCS			
Voltage		220V			
Machine speed		0-2000rpm			
Weight		650KG			
Dimensions (L*W*H)			2M*1.05	M*2.15M	

1.Full computer electronic drive servo system	1 set
2.Main drive servo motor	3.8KW
3. Tape collection, glue wire feeding, ammonia wheel servo motor	0.75KW
4.Single-layer rubber rubber thread, spandex conveyor	1 set
5.Rear Weft Aorn Glue Stable Conveyor	1 set
6.Standard single roll rubber roller drop belt rack	1 set
7.Three-color indicator light (normal startup, yarn breakage, normal shutdown)	1 set

To know more, please visit the website

Enterprise official website: www.huafangdg.com

Alibaba: https://huafang588.1688.com https://huafangdg.en.alibaba.com

HF-609/B3

High -speed plane hook compilation machine

It is suitable for producing all kinds of elastic and non-elastic belts, bra lace belts, medical bandages, clothing belts, zipper belts, sports belts, etc.





Technical Parameters				
Operating width		600mm		
Corresponding	Needle	15	20	24
number of stitches	Needle position	360	480	560
Bar number of weft		3 PCS		
Voltage		220V / 380V		
Machine speed		0-2000rpm		
Weight		450KG		
Dimensions (L*W*H)		2M*1.05M*2.15M		

1. Frequency converter and control device	1set
2. Main drive motor (servo motor)	1.5KW
3. Two-layer weft yarn conveyor group	Group 1
4. Belt drop rack group	Group 1
5. Front pan head rack group (excluding pan head)	Group 1
6. Yarn breaking self-stop device	1set
7.Three-color indicator light (normal startup, yarn breakage, normal shutdown)	1set

To know more, please visit the website

Enterprise official website: www.huafangdg.com

HF-609/B8

Fancy hook machine

It is suitable for producing all kinds of elastic and non-elastic belts, bra lace belts, medical bandages, clothing belts, zipper belts, sports belts, etc.





Technical Param	eters			
Operating width			600mm	
Corresponding	Needle	15	20	24
number of stitches	Needle position	360	480	560
Bar number of weft		8 PCS		
Voltage		220V / 380V		
Machine speed		0-2000rpm		
Weight		600KG		
Dimensions (L*W*H)		2M*1.05M*2.15M		

Frequency converter and control device	1set
2. Main drive motor (servo motor)	1.5KW
3. Two-layer weft yarn conveyor group	Group 1
4. Belt drop rack group	Group 1
5. Front pan head rack group (excluding pan head)	Group 1
Yarn breaking self-stop device	1set
7.Three-color indicator light (normal startup, yarn breakage, normal shutdown)	1set

To know more, please visit the website

Enterprise official website: www.huafangdg.com
Alibaba: https://huafang588.1688.com https://huafangdg.en.alibaba.com

HF-609/B12

Fancy hook machine

It is suitable for producing all kinds of elastic and non-elastic belts, bra lace belts, medical bandages, clothing belts, zipper belts, sports belts, etc.





Technical Parameters				
Operating width		600mm		
Corresponding	Needle	15	20	24
number of stitches	Needle position	360	480	560
Bar number of weft		11 PCS		
Voltage		220V / 380V		
Machine speed		0-2000rpm		
Weight		615KG		
Dimensions (L*W/*LI)		21	4*1 O5M*2 1	51.4

Frequency converter and control device	1set
2. Main drive motor (servo motor)	1.5KW
Two-layer weft yarn conveyor group	Group 1
4. Belt drop rack group	Group 1
5. Front pan head rack group (excluding pan head)	Group 1
Yarn breaking self-stop device	1set
7.Three-color indicator light(normal startup, yarn breakage, normal shutdown)	1set
8. Heavy roller set	1set

To know more, please visit the website

Enterprise official website: www.huafangdg.com

HF-CT609/B8

Computer jacquard hook compilation machine

It is suitable for producing all kinds of elastic and non-elastic belts, bra lace belts, medical bandages, clothing belts, zipper belts, sports belts, etc.



Operating width			600mm		
Corresponding	Needle	15	20	24	
number of stitches	Needle position	360	480	560	
Bar number of weft		8 PCS			
Voltage		220V / 380V			
Machine speed			0-2000rpm		
Weight		900KG			
Dimensions (L*W*H)		2	M*1.05M*2.15	5M	

Frequency converter and control device	1set
2. Main drive motor (servo motor)	1.5KW
3. Two-layer weft yarn conveyor group	Group 1
4. Belt drop rack group	Group 1
5. Front pan head rack group (excluding pan head)	Group 1
6. Yarn breaking self-stop device	1set
7.Three-color indicator light (normal startup, yarn breakage, normal shutdown)	1set

To know more, please visit the website

Enterprise official website: www.huafangdg.com

Alibaba: https://huafang588.1688.com https://huafangdg.en.alibaba.com

HF-CT609/B16

Computer jacquard hook compilation machine

It is suitable for producing all kinds of elastic and non-elastic belts, bra lace belts, medical bandages, clothing belts, zipper belts, sports belts, etc.



Operating width		600mm		
Corresponding	Needle	15	20	24
number of stitches	Needle position	360	480	560
Bar number of weft		16 PCS		
Voltage		220V / 380V		
Machine speed		0-2000rpm		
Weight		950KG		
Dimensions (I *W*H)		21	/*1.05M*2.1	5M

Frequency converter and control device	1set
2. Main drive motor (servo motor)	1.5KW
3. Two-layer weft yarn conveyor group	Group 1
4. Belt drop rack group	Group 1
5. Front pan head rack group (excluding pan head)	Group 1
6. Yarn breaking self-stop device	1set
7.Three-color indicator light (normal startup, yarn breakage, normal shutdown)	1set

To know more, please visit the website

Enterprise official website: www.huafangdg.com

HF-CT610/ACO

Composite computer hook compilation machine

It is suitable for producing all kinds of elastic and non-elastic belts, bra lace belts, medical bandages, clothing belts, zipper belts, sports belts, etc.











Operating width		600mm		
Corresponding number of stitches	Needle	15	20	24
	Needle position	360	480	560
Bar number of weft		10 PCS		
Voltage Machine speed Weight Dimensions (L*W*H)		220V / 380V 0-2000rpm		
		21	V*1.05M*2.1	5M

1. Frequency converter and control device	1set
2. Main drive motor (servo motor)	1.5KW
3. Two-layer weft yarn conveyor group	Group 1
Belt drop rack group	Group 1
5. Front pan head rack group (excluding pan head)	Group 1
Yarn breaking self-stop device	1set
7.Three-color indicator light (normal startup, yarn breakage, normal shutdown)	1set

To know more, please visit the website

Enterprise official website: www.huafangdg.com
Alibaba: https://huafang588.1688.com https://huafangdg.en.alibaba.com

HF-610/AC0

Composite needle hook compilation machine

It is suitable for producing all kinds of elastic and non-elastic belts, bra lace belts, medical bandages, clothing belts, zipper belts, sports belts, etc.











Technical Param	eters			
Operating width			600mm	
Corresponding number of stitches	Needle	15	20	24
	Needle position	360	480	560
Bar number of weft		8 PCS		
Voltage		220V / 380V		
Machine speed		0-2000rpm		
Weight		615KG		
Dimensions (L*W*H)		2M*1.05M*2.15M		

Frequency converter and control device	1set
2. Main drive motor (servo motor)	1.5KW
Two-layer weft yarn conveyor group	Group 1
4. Belt drop rack group	Group 1
5. Front pan head rack group (excluding pan head)	Group 1
6. Yarn breaking self-stop device	1set
7.Three-color indicator light(normal startup, yam breakage, normal shutdown)	1set
8. Heavy roller set	1set

To know more, please visit the website

Enterprise official website: www.huafangdg.com

HF-L2003

Real -time monitoring Copy Term

Real-time monitoring and copying high-speed arrangers are newly developed high-performance arrangers. This machine has a high-quality closed-loop tension control system (PID) to ensure the constant and accuracy of the total tension of the gauze. The microcomputer control system of this machine can continuously monitor the diameter of the plate head in the process of tension and perform tension control in real time to ensure that the diameter (peripheral length) of the set head head (perimeter length) and rice length are consistent.





Technical Parameters

Line speed	100-1000m/minute
Header specification	350*255,400*305, etc.
control method	Real -time control and display of the computer
Tension	PID real -time closed -loop adjustment yarn tension
Holding, clamping and main brakes	Pneumatic control

/lain motor	7.5KW Ventuction Convection Speed Closed Conduction Control
Braking torque	1600 Nm
as source	6 bar
Copy accuracy	When the number of circles is consistent with the outer peripheral length, the rice number error ≤5m
Asy counting	99999m (volume)

To know more, please visit the website

Enterprise official website: www.huafangdg.com
Alibaba: https://huafang588.1688.com https://huafangdg.en.alibaba.com

Precision collateral machine

The precision collateral machine is suitable for loose and tight collaterals of various raw materials such as silk, hemp, yarn, lines, etc., and comprehensively adopts intelligent digital control technology, single ingot, single motor, single frequency conversion, high output, less loss, low noise, low nois









Technical Parameters

	Wound form	Precision row		
	Mechanical speed	600m/min (process speed depends and process parameters)		
	Roll shape	Obluding edge amplitude arbitrarily adjustable		
	Horizontal movement	125-250mm unparalleled variable and variable		
	Volume roll load diameter	Maximum 280mm		
	Roll quality	4KG (can be adjusted according to density)		
	Raw material	Various industrial silk threads such as nylon, polyester, network wire, wrap, short fi ber yam and other industrial silk threads		

Roll tube	Circular tube and pagoda tube optiona
Layout	Single -sided machine
Number of ingots per section	4 ingot
Min/max number of ingots	4/60
Ingot distance	350mm
transmission	Single ingot single control
Installed power	195W/ingot



Scope of application:

Specializing in the production equipment for elastic Baogen line production. Suitable for different open lengths, different thickness and different tensile strengths.

Applicable raw materials: spandex wraps, rubber band wraps, etc.



Scope of application:

Suitable for high -quality tissue of various elastic and non - elastic varns.

Applicable raw materials: polyester, Fulun, nylon, PP, etc.

Applicable menstrual specifications: Φ350x255mm Φ400x255mm

HF-W 401

HF-W 301

To know more, please visit the website

Enterprise official website: www.huafangdg.com

Auxiliary equipment



HF-S 101-1

Scope of application:

It is suitable for different yarns such as trademarks, webbing, lace, and wire. Use lace, traditional horse machines, high -speed woven machines are

woven machines, etc.
Suitable for various yarns: large and small chemical fiber,
Todolong, nylon, golden shallots, etc.



HF-P 101

Scope of application:

It is suitable for consolidation packaging of various elastic nonelastic bands, such as trademarks, lace bands, loose bands, clothing bands, etc.



HF-S 305

Scope of application:

It is suitable for the upper and perflate of various elastic and non-elastic thickness belts, broadband and other fabrics. According to customer needs, the models are divided into electric and steam



HF-P 201

Scope of application:

Suitable for laying and packaging elasticity and non -elastic bands. Such as lace bands, elastic bands, belts, band bands, etc.

To know more, please visit the website

Enterprise official website: www.huafangdg.com
Alibaba: https://huafang588.1688.com https://huafangdg.en.alibaba.com

Production workshop and warehouse



















To know more, please visit the website

Enterprise official website: www.huafangdg.com
Alibaba: https://huafang588.1688.com https://huafangdg.en.alibaba.com